

N72-19961

NASA TECHNICAL MEMORANDUM

NASA TM X-64644

ACCELERATION LEVELS ON THE HEAT FLOW AND
CONVECTION DEMONSTRATION — APOLLO 14

By Eva Gatewood, Marvin G. Morris, and Robert L. Holland
Space Sciences Laboratory

February 11, 1972

**CASE FILE
COPY**

NASA

*George C. Marshall Space Flight Center
Marshall Space Flight Center, Alabama*

1. REPORT NO. NASA TM X-64644	2. GOVERNMENT ACCESSION NO.	3. RECIPIENT'S CATALOG NO.	
4. TITLE AND SUBTITLE Acceleration Levels on the Heat Flow and Convection Demonstration — Apollo 14		5. REPORT DATE February 11, 1972	
		6. PERFORMING ORGANIZATION CODE	
7. AUTHOR(S) Eva Gatewood, Marvin G. Morris, and Robert L. Holland		8. PERFORMING ORGANIZATION REPORT #	
9. PERFORMING ORGANIZATION NAME AND ADDRESS George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama 35812		10. WORK UNIT NO.	
		11. CONTRACT OR GRANT NO.	
		13. TYPE OF REPORT & PERIOD COVERED Technical Memorandum	
12. SPONSORING AGENCY NAME AND ADDRESS National Aeronautics and Space Administration Washington, D. C. 20546		14. SPONSORING AGENCY CODE	
15. SUPPLEMENTARY NOTES Prepared by Space Sciences Laboratory, Science and Engineering			
16. ABSTRACT The method and data for determining the accelerations on the Heat Flow and Convection Demonstration are presented. From the analysis, it is concluded that accelerations as low as $10^{-2} \mu g$ can be detected by using the attitude look angles to the earth and sun, the Apollo trajectory ephemeris, and the ephemeris of the sun.			
17. KEY WORDS Heat flow and convection Apollo Acceleration gradients		18. DISTRIBUTION STATEMENT Unclassified - Unlimited <i>Robert L. Holland</i> 3-2-72	
19. SECURITY CLASSIF. (of this report) Unclassified	20. SECURITY CLASSIF. (of this page) Unclassified	21. NO. OF PAGES 19	22. PRICE \$3.00

TABLE OF CONTENTS

	Page
INTRODUCTION	1
THE METHOD	1
Centrifugal Acceleration	1
Gravity Gradient	2
Internal Mass Distribution	3
THE PROBABLE ERROR	3
THE DATA	4
CONCLUSIONS	4
REFERENCES	14

ACKNOWLEDGEMENTS

The authors are grateful to personnel at MSC and MSFC for providing the trajectory and attitude ephemerides and running the computer programs for this analysis. In particular, we would like to thank Mr. Don Incerto of the Mission Planning and Analysis Division, MSC, who assisted in providing the tapes and, also, Mr. Chuck Finch of the Guidance and Control Division who provided information on the sensitivity and resolution of the attitude sensing and control system. We would also like to thank Miss Sylvia Bryant, MSFC Computation Laboratory, for her patient assistance in debugging the program. Also, Mr. Ray Dell'osso, MSC, was very helpful in providing the location and orientation of the heat flow and convection demonstration within the command module.

ACCELERATION LEVELS ON THE HEAT FLOW AND CONVECTION DEMONSTRATION - APOLLO 14

INTRODUCTION

This report gives a brief description of the method used to determine the acceleration levels on the heat flow and convection demonstration and the flight data results. The sources of acceleration considered included centrifugal acceleration caused by the rotation of the spacecraft about its center of mass, gravity-gradient-induced acceleration caused by the earth and moon, and the internal mass distribution of the spacecraft.

THE METHOD

Centrifugal Acceleration

The centrifugal acceleration is defined as:

$$\ddot{\underline{\rho}} = \dot{\underline{\omega}} \times \underline{\rho} + \underline{\omega} \times (\underline{\omega} \times \underline{\rho}) \quad (1)$$

where $\underline{\rho}$ is the position vector of the center of the heat flow and convection demonstration cell under consideration, $\underline{\omega}$ is the angular velocity vector, and $\dot{\underline{\omega}}$ is the angular acceleration. All quantities are referenced to the command module coordinate axis.

To calculate acceleration values from equation (1), it was necessary to determine the angular velocity vector with respect to space-fixed coordinates and then resolve the components onto the command module axes. This was accomplished by using the look angles to the earth and sun, the trajectory ephemerides of the spacecraft which are given in Reference 1, and the sun's ephemerides which were programmed from the orbital elements given in Reference 2.

Two problems were encountered in attempting to run this program. One was the unexpected zeroes appearing on the trajectory tape in the look-angle positions. After checking this with the personnel in the Mission Planning and Analysis Division of the Manned Spacecraft Center, it was determined that no telemetry data existed at these points; therefore, it was necessary to fill these positions with fictitious data that were taken from the preceding positions to avoid overflows in the computer when dividing. Another problem encountered was the discontinuity that exists in angular quantities obtained by the arctangent of two components of a vector. It was originally thought that this discontinuity occurred at zero; however, it was learned that the subroutine which calculated the arctan had the discontinuity at π rather than zero. Therefore, it was necessary to adjust this part of the program accordingly.

Gravity Gradient

Gravity gradient is defined as:

$$\ddot{\rho} = V, \rho \quad (2)$$

where V , is the gravity gradient matrix

$$V, = \begin{pmatrix} \frac{\partial^2 V}{\partial x^2} & \frac{\partial^2 V}{\partial x \partial y} & \frac{\partial^2 V}{\partial x \partial z} \\ \frac{\partial^2 V}{\partial y \partial x} & \frac{\partial^2 V}{\partial y^2} & \frac{\partial^2 V}{\partial y \partial z} \\ \frac{\partial^2 V}{\partial z \partial x} & \frac{\partial^2 V}{\partial z \partial y} & \frac{\partial^2 V}{\partial z^2} \end{pmatrix}$$

and V is the potential function of the earth or moon which was considered to be a homogeneous sphere, so that

$$V = \frac{GM}{r}$$

where r is the position of the spacecraft in celestial coordinates and GM is the product of the gravitational constant and mass of the earth or moon. This effect is on the order of $10^{-4} \mu g$ for the distance of the command module

from the earth and moon during the time the heat flow and convection demonstration was in progress. This is too low to be detectable with the present accuracy on the look angles to be discussed later.

Internal Mass Distribution

This effect can only be estimated on the basis of the mass and location of each component of the command module and can be expected to be less than $10^{-2} \mu g$ since the acceleration on the surface of a hollow conical shell is this order of magnitude.

A more likely detectable acceleration is the motion of a man inside the spacecraft, since the raising of an arm can cause an acceleration of $10^{-4} g$ to the command module.

THE PROBABLE ERROR

The program that was used was assumed to be a uniform angular rate; however, to assess the probable error, the magnitude of the linear acceleration because of rotation is assumed to be

$$\alpha = \dot{w}r + w^2r .$$

Thus, the probable error in α for a 1-m fixed distance for r is

$$\epsilon_{\alpha} = \sqrt{\epsilon_{\dot{w}}^2 + 4w^2 \epsilon_w^2} \quad (3)$$

where w is the uniform rate, ϵ_w is the probable error in w , and $\epsilon_{\dot{w}}$ is the probable error in \dot{w} .

The numerical differentiation method used for determining the angular velocity, w , from angular position measurements was a 5-point method; thus, the probable error in any one determination is

$$\epsilon_w = \sqrt{\frac{130}{144}} \left(\frac{\epsilon_{\theta}}{\Delta t} \right) \quad (4)$$

where ϵ_θ is the probable error in the angular position ($\simeq 40$ arc-sec) and Δt is the time increment between successive positions (30 s). Thus,

$$\epsilon_w = 5.8 \times 10^{-6} \text{ rad/s} \quad .$$

Using the same error formula [equation (4)] for $\epsilon_{\dot{w}}$ gives

$$\epsilon_{\dot{w}} = 0.95 \frac{\epsilon_w}{30} = 1.8 \times 10^{-7} \text{ rad/s}^2 \quad .$$

Then, from equation (3)

$$\begin{aligned} \epsilon_\alpha &= \sqrt{(1.8 \times 10^{-7})^2 + 4w^2 (5.8 \times 10^{-6})^2} \geq 1.8 \times 10^{-7} \text{ m/s}^2 \\ &= 1.8 \times 10^{-8} \text{ g} = 1.8 \times 10^{-2} \mu \text{ g}. \end{aligned}$$

THE DATA

Figure 1 gives the acceleration in μ g normal to the face of the heat flow and convection demonstration. If the angular rate is on the order of 10^{-4} rad/s, which is the case during the time from 0 to 200 s in Figure 1 (Sheet 1), then the $1\sigma = 1.4826 \epsilon_\alpha$ value on the g curve at this time is $2.7 \times 10^{-2} \mu$ g which is larger than the actual value of g itself. Therefore, it cannot be concluded that this variation is real.

The numbers on the arrows along the time axis indicate the times when zeroes appeared in the attitude look angles which were replaced by the look angles from the preceding record point; thus, the curve within this interval should not be considered real.

CONCLUSIONS

This report has given some indication of the accuracy that can be obtained in determining the accelerations caused by rotation of the spacecraft

by utilizing the attitude and trajectory ephemerides along with the ephemerides of other celestial objects such as the sun, earth, or moon in the case of the Apollo.

The results should not be considered as ultimate real accelerations since the angular accelerations about the center of mass and the linear accelerations of the center of mass were neglected.

Work is still in progress to include these additional accelerations in the program for future flights. These terms were neglected in the initial program because it was thought that they would be much smaller than the others, and, also, a double differentiation of the angular position measurements over 30-s intervals was not considered to be the best method for obtaining the angular accelerations. From the error analysis, it became apparent that the angular acceleration is significant, and it will be included in future results from the program.




Figure 1. Acceleration in μg normal to the face of the heat flow and convection demonstration (Sheet 1 of 15)




Figure 1. (Sheet 2 of 15)




Figure 1. (Sheet 3 of 15)




Figure 1. (Sheet 4 of 15)




Figure 1. (Sheet 5 of 15)




Figure 1. (Sheet 6 of 15)




Figure 1. (Sheet 7 of 15)




Figure 1. (Sheet 8 of 15)




Figure 1. (Sheet 9 of 15)




Figure 1. (Sheet 10 of 15)




Figure 1. (Sheet 11 of 15)




Figure 1. (Sheet 12 of 15)




Figure 1. (Sheet 13 of 15)




Figure 1. (Sheet 14 of 15)




Figure 1. (Sheet 15 of 15)

REFERENCES

1. CSM Zero-g Experiment Trajectory. Computation and Analysis Division, Manned Spacecraft Center, Houston, Texas, January 31, 1971.
2. 1961 Explanatory Supplement to the Ephemeris by the Nautical Almanac. Offices of the United Kingdom and the U. S. A.

February 11, 1972

APPROVAL


TM X-64644

ACCELERATION LEVELS ON THE HEAT FLOW AND CONVECTION DEMONSTRATION - APOLLO 14


By Eva Gatewood, Marvin G. Morris, and Robert L. Holland

The information in this report has been reviewed for security classification. Review of any information concerning Department of Defense or Atomic Energy Commission programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

This document has also been reviewed and approved for technical accuracy.



ROBERT J. NAUMANN
Chief, Physics and Astrophysics Division



GERHARD B. HELLER
Director, Space Sciences Laboratory

DISTRIBUTION

INTERNAL

DIR

Dr. E. Rees

DEP-T

Dr. W. Lucas

AD-S

Dr. E. Stuhlinger

S& E-DIR

Dr. H. Weidner
Mr. B. Montgomery

S& E-R-DIR

Dr. W. Johnson

PD-MP-P

Mr. H. Dudley
Mr. K. Hudson

PM-SAT-E

Mr. L. Ginn

S& E-CSE-DIR

Dr. W. Haeussermann

S& E-COMP-DIR

Dr. H. Hoelzer

S& E-COMP-DS

Mr. J. Lynn
Miss S. Bryant

S& E-COMP-RRF

Mr. F. Rodrigue

S& E-ASTR-A

Mr. H. Hosenthien

S& E-SSL-DIR

Mr. G. Heller
Mr. R. Hembree

S& E-SSL-X

Dr. J. Dozier

S& E-SSL-S

Mr. H. Williams

S& E-SSL-T

Mr. W. Snoddy
Mr. T. Bannister

S& E-SSL-P

Dr. R. Naumann

S& E-SSL-PM

Mr. R. Holland (15)
Miss E. Gatewood
Mr. J. Parker
Mr. W. Darbro
Mr. J. Hintze

S& E-SSL-C

Reserve (15)

PM-PR-M

A& TS-MS-IP (2)

A& TS-MS-IL (8)

A& TS-MS-H

A& TS-TU (6)

A& TS-PAT

Mr. L. Wofford

S& E-ASTR-G

Dr. G. Doane

EXTERNAL

National Aeronautics and Space Administration

Washington, D. C. 20546
ATTN: Mr. R. Bryson, MAL
Mr. F. Roberson, MAL
Mr. W. Keller, SL

Jet Propulsion Laboratory
California Institute of Technology
4800 Oak Grove Drive
Pasadena, California 91103
ATTN: Mr. Paul Muller
Dr. E. Sherry
Mr. E. Christensen

Department of Aeronautics &
Astronautics
Stanford University
Stanford, California 94305
ATTN: Dr. D. DeBra
Dr. J. Breakwell

Smithsonian Astrophysical Observatory
60 Garden Street
Cambridge, Massachusetts 02139
ATTN: Dr. C. Lundquist
Dr. G. Colombo

Grumman Aircraft Engineering Corporation
Bethpage, New York 11714
ATTN: Dr. P. Savet

Hughes Research Laboratories
3011 Malibu Canyon Road
Malibu, California 90265
ATTN: Dr. R. Forward
Mr. D. Sypma
Mr. C. Bell

Massachusetts Institute of Technology
Charles Stark Draper Laboratories
68 Albany Street
Cambridge, Massachusetts 02139
ATTN: Mr. M. Tragreser

Air Force Cambridge Research Laboratories
Lawrence G. Hanscom Field
Bedford, Massachusetts 01730
ATTN: Mr. D. Anthony
Dr. Bela Zabo

NASA
Manned Spacecraft Center
Houston, Texas 77058
ATTN: Mr. W. Wollenhaupt, FM4
Mr. D. Incerto, FM13
Mr. C. Finch, EG7

NASA
Langley Research Center
Hampton, Virginia 23365
ATTN: Mr. A. Beswick, 473

Lockheed Missiles & Space Co.
Research Park
Huntsville, Alabama 35807
ATTN: Dr. C. Fan
Dr. P. Grodzka
Mr. R. Heddon

Teledyne Brown Engineering
Sparkman Drive
Huntsville, Alabama 35807
ATTN: Miss M. Mullins

Scientific and Technical Information Facility (25)
P. O. Box 33
College Park, Maryland 20740
ATTN: NASA Representative (S-AK/RKT)